



Consumer Products Division

76 Maple Avenue
Northport, NY 11768
Phone: 631-261-8764
Fax: 631-980-3945
Email: info@bitstld.net
Web Site: <http://bitstld.net>

SCGx Series Smart Strip Power Strips

SCG3, SCG4 & SCG5

Surge Protector Specifications:

- Recessed, lighted power switch
- Pat. Pending Combined ground & surge protector status indicator
- Switched outlet indicator
- 6-Foot 14 gauge heavy-duty power cord
- 45 degree angled space saver plug
- Wall Mountable in all 4 directions
- 7 outlets total
 - 1 Control outlet – always hot
 - 2 Constant hot outlets
 - 4 Switched outlets – 1 transformer
- UL 1449 rating
- 120 Volt 50/60 Hz
- 1225 joules protection
 - 775 joules live to neutral
 - 225 joules live to ground
 - 225 joules neutral to ground
- 48,000 amp three-way Protection
 - 24,000 amps live to neutral
 - 12,000 amps live to ground
 - 12,000 amps neutral to ground
- 330 volt, three-way protection
- 15 amp circuit breaker
- 4 different fuses:
 - 2 Thermal & current fuses
 - 2 Trace land fuses
- EMI/RFI filtering:
 - .1ufd film box capacitor
 - Up to 40db line noise reduction

SCG3, SCG4 & SCG5

Energy Saver Specifications:

- Ultra safe passive current sensor
- Patented protective hysteresis circuit
- 2 RC filters eliminate false switching
- Uses ZERO POWER when the switched outlets are off
- Uses less than 1 watt when fully energized

SCG4 Fax/Modem Specifications:

- RJ12 connectors for standard phones
- Primary line surge protection
- 100% Compatible with both single-line and two-line phones
- Two ultra-fast sideactors protect against fast-rising high-voltage spikes
- 312 volt clamping
- Twin fuses to protect against long-duration voltage spikes
- 6-foot Phone Cord Included

SCG5 Coax Specifications:

- Fully shielded
- 0-1.2 GHz Frequency response
- 2 Gold plated F-connectors
- Works with all antenna, cable & satellite systems